



# UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE  
United States Patent and Trademark Office  
Address: COMMISSIONER FOR PATENTS  
P.O. Box 1450  
Alexandria, Virginia 22313-1450  
www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/717,917	11/21/2003	Toshihide Tsubata	1035-482	7569

23117 7590 01/24/2007  
NIXON & VANDERHYE, PC  
901 NORTH GLEBE ROAD, 11TH FLOOR  
ARLINGTON, VA 22203

EXAMINER
----------

SHERMAN, STEPHEN G

ART UNIT	PAPER NUMBER
----------	--------------

2629

SHORTENED STATUTORY PERIOD OF RESPONSE	MAIL DATE	DELIVERY MODE
3 MONTHS	01/24/2007	PAPER

**Please find below and/or attached an Office communication concerning this application or proceeding.**

If NO period for reply is specified above, the maximum statutory period will apply and will expire 6 MONTHS from the mailing date of this communication.

## Office Action Summary

Application No.

10/717,917

Applicant(s)

TSUBATA ET AL.

Examiner

Stephen G. Sherman

Art Unit

2629

-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --

### Period for Reply

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE 3 MONTH(S) OR THIRTY (30) DAYS, WHICHEVER IS LONGER, FROM THE MAILING DATE OF THIS COMMUNICATION.

- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.
- If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
- Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133). Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).

### Status

- 1) ☒ Responsive to communication(s) filed on 20 December 2006.
- 2a) ☐ This action is **FINAL**. 2b) ☒ This action is non-final.
- 3) ☐ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

### Disposition of Claims

- 4) ☒ Claim(s) 1 and 3-34 is/are pending in the application.
- 4a) Of the above claim(s) \_\_\_\_\_ is/are withdrawn from consideration.
- 5) ☐ Claim(s) \_\_\_\_\_ is/are allowed.
- 6) ☒ Claim(s) 1 and 3-34 is/are rejected.
- 7) ☐ Claim(s) \_\_\_\_\_ is/are objected to.
- 8) ☐ Claim(s) \_\_\_\_\_ are subject to restriction and/or election requirement.

### Application Papers

- 9) ☐ The specification is objected to by the Examiner.
- 10) ☒ The drawing(s) filed on 20 December 2006 is/are: a) ☒ accepted or b) ☐ objected to by the Examiner.  
Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).  
Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).
- 11) ☐ The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.

### Priority under 35 U.S.C. § 119

- 12) ☒ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).
- a) ☒ All b) ☐ Some \* c) ☐ None of:
- 1) ☒ Certified copies of the priority documents have been received.
  - 2) ☐ Certified copies of the priority documents have been received in Application No. \_\_\_\_\_.
  - 3) ☐ Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).

\* See the attached detailed Office action for a list of the certified copies not received.

### Attachment(s)

- 1) ☐ Notice of References Cited (PTO-892)
- 2) ☐ Notice of Draftsperson's Patent Drawing Review (PTO-948)
- 3) ☒ Information Disclosure Statement(s) (PTO/SB/08)  
Paper No(s)/Mail Date \_\_\_\_\_
- 4) ☐ Interview Summary (PTO-413)  
Paper No(s)/Mail Date \_\_\_\_\_
- 5) ☐ Notice of Informal Patent Application
- 6) ☐ Other: \_\_\_\_\_

### **DETAILED ACTION**

1. This office action is in response to the amendment filed the 20 December 2006. Claims 1 and 3-34 are pending. Claim 2 has been cancelled.

### ***Response to Arguments***

2. Applicant's arguments with respect to claims 1 and 3-20 have been considered but are moot in view of the new ground(s) of rejection.

### ***Claim Objections***

3. Claim 4 is objected to because of the following informalities: Claim 4 recite the limitation of "a light shielding film," however, claim 1 was amended to have the light shielding film limitation already claimed, so instead of reciting "a light shielding film" in claim 4, "the light shielding film" should be claimed. Appropriate correction is required.

### ***Claim Rejections - 35 USC § 112***

4. The following is a quotation of the first paragraph of 35 U.S.C. 112:

The specification shall contain a written description of the invention, and of the manner and process of making and using it, in such full, clear, concise, and exact terms as to enable any person skilled in the art to which it pertains, or with which it is most nearly connected, to make and use the same and shall set forth the best mode contemplated by the inventor of carrying out his invention.

5. Claims 12, 15 and 18 are rejected under 35 U.S.C. 112, first paragraph, as failing to comply with the enablement requirement. The claim(s) contains subject matter which was not described in the specification in such a way as to enable one skilled in the art to which it pertains, or with which it is most nearly connected, to make and/or use the invention.

Claims 12, 15 and 18 state that the light shielding film is made of metal, however, claims 1, 13 and 18 from which these claims depend state that the light shielding film has an insulating property. Since metals are conductors, not insulators, it is not possible to make the light shielding film to be made of metal and still have an insulating property.

6. The following is a quotation of the second paragraph of 35 U.S.C. 112:

The specification shall conclude with one or more claims particularly pointing out and distinctly claiming the subject matter which the applicant regards as his invention.

7. Claims 1 and 26 are rejected under 35 U.S.C. 112, second paragraph, as being indefinite for failing to particularly point out and distinctly claim the subject matter which applicant regards as the invention.

Claim 1 states the limitation: "a gap covered by only a layer having an insulating property is provided between the signal line and the pixel electrode, and the layer having the insulating property and covering the gap includes a light shielding film..."

This limitation is indefinite because it is unclear as to whether the claim intends for there

to only be one layer in view of the vertical direction through the gap or whether the claim intends for there to be two layers in view of the vertical direction, one being the insulating layer and one being the light shielding film, i.e. black matrix. Furthermore, Figures 1, 3 and 4 of the applicant's specification show that there are multiple layers in view of the vertical direction and not just a layer. Therefore, it is unclear whether the specification is correct and the claim is wrong or whether the claim is right and the specification is wrong. For the purposes of examination, the examiner will assume that the Figures are correct and there is indeed multiple layers, not just one layer, in view of the vertical direction.

Claim 26 states the limitation: "wherein the desired  $\Delta\Delta\beta$  value is not more than 0.08, is preferably not more than 0.04, and is preferably not more than 0.01." This claim is indefinite because it is unclear as to whether the desired value is not more than 0.04 or is not more than 0.01. Furthermore, the examiner notes that the word "preferably" is also indefinite because it is unclear as to whether the value is less than 0.04 or more than 0.04 or the value is less than 0.01 or more than 0.01.

### ***Claim Rejections - 35 USC § 103***

8. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:

(a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the

Art Unit: 2629

invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negated by the manner in which the invention was made.

9. The factual inquiries set forth in *Graham v. John Deere Co.*, 383 U.S. 1, 148 USPQ 459 (1966), that are applied for establishing a background for determining obviousness under 35 U.S.C. 103(a) are summarized as follows:

1. Determining the scope and contents of the prior art.
2. Ascertaining the differences between the prior art and the claims at issue.
3. Resolving the level of ordinary skill in the pertinent art.
4. Considering objective evidence present in the application indicating obviousness or nonobviousness.

10. Claims 1, 4, 6, 8, 10, 13, 16, 19-22, 24-25, 27 are rejected under 35 U.S.C. 103(a) as being unpatentable over AAPA (Page 1, line 8, to page 9, line 2 of the specification and Figures 12 and 13) in view of Matsuo (JP 07-128685).

**Regarding claim 1**, AAPA discloses a display device substrate (Figure 13, item 110), comprising:

one or more pixel electrodes each of which is provided on each intersection of a signal line and a scanning line that are provided on an insulating substrate (Figures 12 and 13 show that pixel electrode 103' is located at the intersection of scanning line 104 and a signal line 102, and are provided on substrate 110, which it explained to be insulating on page 5, lines 16-20.); and

an interlayer insulating film stacked between the signal line and the pixel electrode (Figure 13 shows interlayer insulating film layer 115 between the signal line 102 and the pixel electrode 103').

wherein in view of a vertical direction with respect to the surface of the insulting substrate, only a layer having an insulating property is provided between the signal line and the pixel electrode (Figure 13 shows that only layer 115 is between pixel electrode 103' and signal line 102, where page 6, lines 16-17 explain that layer 115 is an insulating layer.), and the layer having the insulating property includes a light shielding film having an insulating property (Figure 13 shows that layer 115 includes light shielding film 108, and is explained to having an insulating property on page 6, lines 4-9.).

AAPA fails to teach that in view of a vertical direction with respect to a surface of the insulating substrate, the signal line is provided on an area on which the pixel electrode is not provided, and a gap is provided between the signal line and the pixel electrode.

Matsuo discloses a display device substrate (Drawing 2, substrate 9) where in view of a vertical direction with respect to a surface of the insulating substrate, the signal line is provided on an area on which the pixel electrode is not provided, and a gap is provided between the signal line and the pixel electrode (Drawings 1 and 2 shows that there is a gap between the signal lines 2 and the pixel electrode 3.).

Therefore it would have been obvious to "one of ordinary skill" in the art at the time the invention was made to provide a gap between the signal line and the pixel electrode as taught by Matsuo with the substrate structure taught by AAPA in order to reduce capacitive coupling of a pixel electrode and a source that causes unevenness and crosstalk of the vertical direction.

**Regarding claim 4**, AAPA and Matsuo disclose the display device substrate as set forth in claim 1.

Matsuo also discloses a display device substrate further comprising:

an active element provided on each intersection of the signal line and the scanning line (Drawings 1 and 2 and paragraphs [0003] and [0011] explain that the active region 10 is provided at a junction between the scanning lines 1 and signal lines 2.);

a light shielding film provided so as to cover at least a surface of the signal line among the signal line, the active element, and the scanning line (Drawings 1 and 2 show that light shielding film 8 covers the signal lines 2, the active element 10 and the scanning line 1.), wherein

in view of the vertical direction with surface of the insulating substrate, respect to the a gap between the pixel electrodes which are adjacent to each other with the signal line there between is covered by the light shielding film (Drawings 1 and 2 show that the gap between the pixel electrode 3 is covered by the light shielding film 8.).

**Regarding claim 6**, AAPA and Matsuo disclose the display device substrate as set forth in claim 1.

Matsuo also disclose a display device substrate further comprising:

an active element provided on each intersection of the signal line and the scanning line (Drawings 1 and 2 and paragraphs [0003] and [0011] explain that the



active region 10 is provided at a junction between the scanning lines 1 and signal lines 2.); and

a light shielding film provided so as to cover at least a surface of the signal line among the signal line, the active element, and the scanning line (Drawings 1 and 2 show that light shielding film 8 covers the signal lines 2, the active element 10 and the scanning line 1.), wherein

in view of the vertical direction with respect to the surface of the insulating substrate, (i) the light shielding film which covers the surface of the signal line film and (ii) the pixel electrode overlap with each other (Drawings 1 and 2 show that the pixel electrodes 3 and the light shielding film 8 overlap each other.).

**Regarding claim 8**, AAPA and Matsuo disclose the display device substrate as set forth in claim 1.

Matsuo also discloses a display device substrate further comprising:

an active element provided on each intersection of the signal line and the scanning line (Drawings 1 and 2 and paragraphs [0003] and [0011] explain that the active region 10 is provided at a junction between the scanning lines 1 and signal lines 2.);

a contact hole for allowing the active element and the pixel electrode to be in contact with each other (Drawings 1 and 2 show that a contact hole electrically connects active portion 10 to pixel electrode 3, as explained in paragraphs [0003] and [0011].); and

a light shielding film provided so as to cover surfaces of the active element, the signal line, and the scanning line (Drawings 1 and 2 show that light shielding film 8 covers the signal lines 2, the active element 10 and the scanning line 1.), wherein

in view of the vertical direction with respect to the surface of the insulating substrate, (i) the light shielding film which covers the surface of the signal line film and (ii) the pixel electrode overlap with each other (Drawings 1 and 2 show that the pixel electrodes 3 and the light shielding film 8 overlap each other.).

**Regarding claim 10**, AAPA and Matsuo disclose the display device substrate as set forth in claim 1.

Matsuo also disclose a display device substrate further comprising:

an active element provided' on each intersection of the signal line and the scanning line (Drawings 1 and 2 and paragraphs [0003] and [0011] explain that the active region 10 is provided at a junction between the scanning lines 1 and signal lines 2.);

a contact hole for allowing the active element and the pixel electrode to be in contact with each other (Drawings 1 and 2 show that a contact hole electrically connects active portion 10 to pixel electrode 3, as explained in paragraphs [0003] and [0011].);  
and

a light shielding film provided so as to cover at least a surface of the signal line among the signal line, the active element, and the scanning line (Drawings 1 and 2

show that light shielding film 8 covers the signal lines 2, the active element 10 and the scanning line 1.), wherein;

the interlayer insulating film is a stacking body of two or more layers, and the light shielding film is stacked between an uppermost layer and a lowermost layer that constitute the made interlayer insulating film (Drawings 1 and 2 show that the interlayer insulating film is made of layers 12, 13 and 14, where the light shielding film is stack between the uppermost layer 14 and a lowermost layer 12.), and

in view of the vertical direction with respect to the surface of the insulating substrate, a gap between the pixel electrodes which are adjacent to each other with the signal line there between is covered by the light shielding film (Drawings 1 and 2 show that the gap between the pixel electrode 3 is covered by the light shielding film 8.).

***Regarding claim 13***, AAPA and Matsuo disclose the display device substrate as set forth in claim 1.

Matsuo also discloses a display device substrate further comprising:

an active element provided on each intersection of the signal line and the scanning line (Drawings 1 and 2 and paragraphs [0003] and [0011] explain that the active region 10 is provided at a junction between the scanning lines 1 and signal lines 2.);

a contact hole for allowing the active element and the pixel electrode to be in contact with each other (Drawings 1 and 2 show that a contact hole electrically connects

Art Unit: 2629

active portion 10 to pixel electrode 3, as explained in paragraphs [0003] and [0011].);

and

a light shielding film provided so as to cover at least a surface of the signal line among the signal line, the active element, and the scanning line (Drawings 1 and 2 show that light shielding film 8 covers the signal lines 2, the active element 10 and the scanning line 1.), wherein:

the interlayer insulating film is a stacking body made of two or more layers, and the light shielding film is stacked between an uppermost layer and a lowermost layer that constitute the interlayer insulating film (Drawings 1 and 2 show that the interlayer insulating film is made of layers 12, 13 and 14, where the light shielding film is stack between the uppermost layer 14 and a lowermost layer 12.), and

in view of the vertical direction with respect to the surface of the insulating substrate, (i) the light shielding film which covers the surface of the signal line film and (ii) the pixel electrode overlap with each other (Drawings 1 and 2 show that the pixel electrodes 3 and the light shielding film 8 overlap each other.).

**Regarding claim 16**, AAPA and Matsuo disclose the display device substrate as set forth in claim 1.

Matsuo also discloses a display device substrate further comprising:

an active element provided on each intersection of the signal line and the scanning line (Drawings 1 and 2 and paragraphs [0003] and [0011] explain that the

Art Unit: 2629

active region 10 is provided at a junction between the scanning lines 1 and signal lines 2.);

a contact hole for allowing the active element and the pixel electrode to be in contact with each other (Drawings 1 and 2 show that a contact hole electrically connects active portion 10 to pixel electrode 3, as explained in paragraphs [0003] and [0011].); and

a light shielding film provided so as to cover surfaces of the active element, the signal line, and the scanning line (Drawings 1 and 2 show that light shielding film 8 covers the signal lines 2, the active element 10 and the scanning line 1.), wherein:

the interlayer insulating film is a stacking body made of two or more layers, and the light shielding film is stacked between an uppermost layer and a lowermost layer that constitute the interlayer insulating film (Drawings 1 and 2 show that the interlayer insulating film is made of layers 12, 13 and 14, where the light shielding film is stack between the uppermost layer 14 and a lowermost layer 12.), and

in view of the vertical direction with respect to the surface of the insulating substrate, (i) the light shielding film which covers the surface of the signal line film and (ii) the pixel electrode overlap with each other (Drawings 1 and 2 show that the pixel electrodes 3 and the light shielding film 8 overlap each other.).

**Regarding claim 19**, AAPA and Matsuo disclose the display device substrate as set forth in claim 1.

Matsuo also disclose wherein the gap is set to be within a range of from not less than 1 $\mu$ m to not more than 20 $\mu$ m (It would be inherent that the gap between the pixel electrode 3 and signal line 2 taught by Mutsumi would be within a range of from not less than 1 $\mu$ m to not more than 20 $\mu$ m.).

**Regarding claim 20**, AAPA and Matsuo disclose a liquid crystal display device, comprising the display device substrate as set forth in claim 1 (Paragraph [0001] of Matsuo).

**Regarding claim 21**, please refer to the rejection of claim 1, and furthermore it would be inherent that there are plural pixel electrodes.

AAPA and Matsuo fail to teach of a size of the gap being set to provide a desired  $\Delta\Delta\beta$  value which is interrelated with display unevenness, however, since when a gap is introduced between the pixel electrodes and signal lines display unevenness is reduced, it would have been an obvious design choice to “one of ordinary skill” in the art at the time the invention was made to optimize the gap to a desired value to provide the best display characteristics possible.

**Regarding claim 22**, AAPA and Matsuo disclose a display device substrate as set forth in claim 21.

Matsuo also discloses a display device substrate further comprising a light shielding film provided over the signal line and the gap (Drawing 2, black matrix 8), the

Art Unit: 2629

pixel electrode being provided over at least a portion of the light shielding film (Drawing 2 shows that pixel electrode 3 is provided over a portion of black matrix 8.).

**Regarding claim 24**, AAPA and Matsuo disclose the device substrate as set forth in claim 22.

Matsuo also discloses a display device substrate further comprising:

an active element provided on each respective intersection of the signal line and the scanning line (Drawings 1 and 2 and paragraphs [0003] and [0011] explain that the active region 10 is provided at a junction between the scanning lines 1 and signal lines 2.);

wherein the light shielding film is provided so as to cover at least a surface of the signal line among the signal line, the active element, and the scanning line (Drawings 1 and 2 show that light shielding film 8 covers the signal lines 2, the active element 10 and the scanning line 1.).

**Regarding claim 25**, AAPA and Matsuo disclose a display device substrate as set forth in claim 22.

AAPA also disclose a display device substrate wherein the light shielding film covers a signal line associated with a first pixel electrode and is overlapped by a second pixel electrode (Figure 13 shows pixel electrode 103 and pixel electrode 103' respectively), the first pixel electrode being directly driven by the signal line and the second pixel electrode not being directly driven by the signal line (Pixel electrode 103 is

connected to the drain and therefore is directly driven and since 103' is not connected it is not directly driven.).

Matsuo also disclose of a display device wherein an overlap of the second pixel electrode and the light shielding film having a width  $y$  (Drawing 2 shows that there is an overlap between the pixel electrode 3 and the black matrix 8 that has some width.).

AAPA and Matsuo fail to teach wherein  $y$  is not less than  $0.6\text{ }\mu\text{m}$  and not more than  $5\text{ }\mu\text{m}$ , however, it would have been an obvious design choice to "one of ordinary skill" in the art at the time the invention was made to optimize the overlap to a desired width in order to provide the best display characteristics possible.

**Regarding claim 27**, AAPA and Matsuo disclose a display device substrate as set forth in claim 21.

AAPA also disclose wherein the interlayer insulating film comprises a stacking body, the stacking body comprising an upper interlayer insulating film and a lower interlayer insulating film (Figure 13 shows interlayer insulating film 115 and 111 which are stacked upon each other on the substrate 110.).

**Regarding claim 28**, AAPA and Matsuo disclose a display device substrate as set forth in claim 27.

AAPA and Matsuo fail to teach wherein the upper interlayer insulating film has a dielectric constant of about 3.7, however it would have been an obvious design choice to "one of ordinary skill" in the art at the time the invention was made to choose an



Art Unit: 2629

insulating film with an optimized dielectric constant so as to provide for the best display characteristics possible depending on the characteristics of the other materials used.

***Regarding claim 29***, AAPA and Matsuo disclose a display device substrate as set forth in claim 27.

AAPA and Matsuo fail to teach wherein the upper interlayer insulating film has a thickness of about 2.5  $\mu\text{m}$ , however it would have been an obvious design choice to “one of ordinary skill” in the art at the time the invention was made to optimize the thickness of the insulating layer to a desired thickness based upon the characteristics of the other materials in order to provide for the best display characteristics possible.

***Regarding claim 30***, AAPA and Matsuo disclose a display device substrate as set forth in claim 21.

AAPA and Matsuo fail to teach wherein the gap has a width in a range of not less than 1  $\mu\text{m}$  and not more than 20  $\mu\text{m}$ , however it would have been an obvious design choice to “one of ordinary skill” in the art at the time the invention was made to optimize the width of the gap to a desired value in order to provide for the best display characteristics possible.

***Regarding claim 31***, AAPA and Matsuo disclose a display device substrate as set forth in claim 21.

AAPA and Matsuo fail to teach wherein the pixel electrodes of the substrate are driven by a dot reversal driving system, however, it is well known in the art to drive liquid crystal displays by a dot reversal driving system.

**Regarding claim 32**, AAPA and Matsuo disclose a display device substrate as set forth in claim 21.

AAPA also discloses a display device substrate further comprising an active device associated with each pixel electrode (Figure 13 shows active element 114), the active device having a gate electrode (Figure 13 shows gate electrode 104) and at least part of a source electrode (Figure 13 shows source electrode 105), the pixel electrode being formed over a gate electrode and at least part of a source electrode of its associated active device (Figure 13 shows that the pixel electrode 103 is formed over the gate and source electrodes 104 and 105.).

**Regarding claim 33**, please refer to the rejection of claims 21-22, and furthermore AAPA also disclose a display device substrate wherein the light shielding film covers a signal line associated with a first pixel electrode and is overlapped by a second pixel electrode (Figure 13 shows pixel electrode 103 and pixel electrode 103' respectively), the first pixel electrode being directly driven by the signal line and the second pixel electrode not being directly driven by the signal line (Pixel electrode 103 is connected to the drain and therefore is directly driven and since 103' is not connected it is not directly driven.).

Matsuo also disclose of a display device wherein an overlap of the second pixel electrode and the light shielding film having a width  $y$  (Drawing 2 shows that there is an overlap between the pixel electrode 3 and the black matrix 8 that has some width.) and whereby a gap of width  $x$  is provided between the signal line and the pixel electrode (Drawing 2 shows that there is a gap between the pixel electrode and the signal line that has some width.).

AAPA and Matsuo fail to teach wherein  $y$  is not less than  $0.6\text{ }\mu\text{m}$  and not more than  $5\text{ }\mu\text{m}$  and wherein  $x$  is in the rang of no less than  $1\text{ }\mu\text{m}$  and not more than  $20\text{ }\mu\text{m}$ , however, it would have been an obvious design choice to “one of ordinary skill” in the art at the time the invention was made to optimize the overlap and gap to desired widths in order to provide the best display characteristics possible.

**Regarding claim 34**, AAPA and Matsuo disclose a display device substrate as set forth in claim 33.

Matsuo also discloses a display device substrate further comprising:

an active element provided on each respective intersection of the signal line and the scanning line (Drawings 1 and 2 and paragraphs [0003] and [0011] explain that the active region 10 is provided at a junction between the scanning lines 1 and signal lines 2.);

wherein the light shielding film is provided so as to cover at least a surface of the signal line among the signal line, the active element, and the scanning line (Drawings 1

Art Unit: 2629

and 2 show that light shielding film 8 covers the signal lines 2, the active element 10 and the scanning line 1.).

11. Claims 3, 5, 7, 9, 11, 14, 17 and 23 are rejected under 35 U.S.C. 103(a) as being unpatentable over Mutsumi (JP 07-128685) in view of Zhang et al. (US 6,396,470).

***Regarding claims 3, 5, 7, 9, 11, 14, 17 and 23,*** AAPA and Matsuo disclose the display device substrate as set forth in claims 2, 4, 6, 8, 10, 13 and 16.

AAPA and Matsuo fail to teach wherein the light shielding film is made of resin having an insulating property.

Zhang et al. disclose of a light shielding film made of resin having an insulating property (Column 12, lines 54-63 explain that the light shielding film shown in Figure 8 is an insulating black resin.).

Therefore it would have been obvious to “one of ordinary skill” ion the art at the time the invention was made that the light shielding film taught by the combination of AAPA and Matsuo be made of an insulating resin as taught by Zhang et al. in order to allow the light shielding film to be forming in a desired area without using a resist mask.

### ***Conclusion***

Art Unit: 2629

12. Any inquiry concerning this communication or earlier communications from the examiner should be directed to Stephen G. Sherman whose telephone number is (571) 272-2941. The examiner can normally be reached on M-F, 8:00 a.m. - 4:30 p.m..

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Amr Awad can be reached on (571) 272-7764. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see <http://pair-direct.uspto.gov>. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free). If you would like assistance from a USPTO Customer Service Representative or access to the automated information system, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.

SS

18 January 2007

AMR A. AWAD  
SUPERVISORY PATENT EXAMINER  
*Amr A. Awad*